

UNCLASSIFIED

AD NUMBER

AD450636

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; 22 OCT 1964.
Other requests shall be referred to Bureau of Yards and Docks, Washington, DC 20350.

AUTHORITY

USNCB ltr dtd 24 oct 1974

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD 4 5 0 6 3 6

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

450636

4 5 0 6 3 6

Technical Note N-652

APPLICATION OF Z-TRANSFORM METHODS TO MARKOV

CHAIN PROBLEMS, WITH A MAINTENANCE EXAMPLE

by

Stephen F. Love

22 October 1964

CATALOGED BY DDC

AS AD NO.

U. S. NAVAL CIVIL ENGINEERING LABORATORY
Port Hueneme, California

DDC
NOV 10 1964
DDC-IRA C

APPLICATION OF Z-TRANSFORM METHODS TO MARKOV
CHAIN PROBLEMS, WITH A MAINTENANCE EXAMPLE
Y-F015-15-06-504

Type C

by

Stephen F. Love

ABSTRACT

This Technical Note develops an application of the theory of the Z-transform to the problem of finding the n th power of a transition matrix, motivated by the need of such a solution in the theory of Markov Chains. To illustrate the theory, an example involving vehicle maintenance is presented in detail. The results of the example may be compared with those of Philip M. Morse, "Markov Processes", in Notes On Operations Research, 1959, The Technology Press, Massachusetts Institute of Technology.

Qualified requesters may obtain copies of this Technical Note from DDC

INTRODUCTION

Often in Markov chain problems it is desired to find the n th power, P^n , of a transition matrix P . P^n can be found by using Z-transforms as follows:

Let Π_n be the row vector,

$$\Pi_n = [\Pi_{1n} , \Pi_{2n} , \dots , \Pi_{mn}]$$

where Π_{jn} is the probability of being in state j after n transitions. (In general, brackets $[\]$ will enclose a matrix or vector.)

Let $P = [P_{ij}]$ be the matrix of transition probabilities of going from state i to state j in one transition.

Then the Markov equation is

$$\Pi_{n+1} = \Pi_n P .$$

In particular,

$$\Pi_1 = \Pi_0 P ,$$

$$\Pi_2 = \Pi_1 P = \Pi_0 P^2 .$$

In general,

$$\Pi_n = \Pi_0 P^n .$$

Let the Z-transform be defined as

$$Z \{ y_n \} = \sum_{n=0}^{\infty} y_n z^n , \text{ assuming that the series converges, where}$$

$\{ y_n \}$ is a sequence of numbers y_0, y_1, y_2, \dots . Since Z is a linear operator,

$$Z (P) = [Z (p_{ij})] ;$$

$$\begin{aligned} \text{so } Z (\Pi_{n+1}) &= \sum_{n=0}^{\infty} \Pi_{n+1} z^n \\ &= \frac{1}{z} \sum_{n=0}^{\infty} \Pi_{n+1} z^{n+1} \end{aligned}$$

$$\begin{aligned}
&= \frac{1}{z} \left(\sum_{n=1}^{\infty} \Pi_n z^n \right) \\
&= \frac{1}{z} \left[\left(\sum_{n=0}^{\infty} \Pi_n z^n \right) - \Pi_0 \right] \\
&= \frac{1}{z} z \left(\Pi_n \right) - \frac{1}{z} \Pi_0
\end{aligned}$$

and, since

$$\begin{aligned}
&\Pi_{n+1} - \Pi_n P = 0 \\
\text{and } z \left(\Pi_n P \right) &= z \left(\Pi_n \right) P, \\
\frac{1}{z} z \left(\Pi_n \right) - \frac{1}{z} \Pi_0 - z \left(\Pi_n \right) P &= 0.
\end{aligned}$$

Multiply by z and transposing Π_0 :

$$\begin{aligned}
z \left(\Pi_n \right) - z z \left(\Pi_n \right) P &= \Pi_0 \\
\text{so } z \left(\Pi_n \right) \cdot [I - z P] &= \Pi_0 \\
\text{and } z \left(\Pi_n \right) &= \Pi_0 [I - z P]^{-1} \text{ if the inverse exists.}
\end{aligned}$$

Taking inverse transforms:

$$\begin{aligned}
\Pi_n &= \Pi_0 z^{-1} \left([I - zP]^{-1} \right) \\
\text{so } P^n &= z^{-1} \left([I - zP]^{-1} \right).
\end{aligned}$$

Hence, we have an algorithm for computing $\left\{ P^n \right\}$, where P^n is the sequence of matrices

$$\left[\left\{ p_{ij}^k \right\} \right]$$

where p_{ij}^k is the element in the i th row and j th column of $[P]^k$, $k = 1, 2, \dots$. Hereafter, the generic term P^n will be used.

A MAINTENANCE EXAMPLE*

A bus makes N runs per week. Suppose there are two stages in the depreciation of the bus; in stage A it can still be operated, but it is apparent that it will soon need to be repaired; in stage B, it cannot do its job and must be repaired. If the bus is repaired when it is discovered to be in stage A of depreciation, the repair is not difficult, but if it is allowed to run until it breaks down (stage B) the repair will take longer. The decision to be made is when to repair the bus.

Suppose the deterioration is random, such that if it is in good condition at the beginning of a run then the probability it will still be in stage A at the end of the run will be a . Similarly, if the bus is in stage A at the beginning of a run, the chance that it will reach stage B by the end of the run is b . For simplicity, let the length of time to repair the bus in stage A be the same length of time it takes to complete one run. If stage B is reached, the bus will be out of commission until the beginning of the following week.

Two alternative maintenance doctrines suggest themselves: Doctrine 1 - repair if the bus reaches stage A; doctrine 2 - wait until stage B is reached to make repairs. The Markov matrices are:

Doctrine 1	Doctrine 2
$A \begin{matrix} & \begin{matrix} A & B \end{matrix} \\ \begin{matrix} A \\ B \end{matrix} & \begin{bmatrix} 1-a & a \\ 1 & 0 \end{bmatrix} \end{matrix}$	$A \begin{matrix} & \begin{matrix} A & B \end{matrix} \\ \begin{matrix} A \\ B \end{matrix} & \begin{bmatrix} 1-a & a \\ 0 & 1-b \\ 0 & 0 \end{bmatrix} \end{matrix}$

To compare the two doctrines, two questions may be posed.

- (1) What is the expected number of runs, n_s , the bus will make if it always starts in good condition?

This is

$$n_z = \sum_{n=0}^{n-1} \sum_{k=1}^M p_{1k}^n \text{ over all states } k \text{ in which the bus may}$$

*Adapted from Morse, Philip M., "Markov Processes", in Notes on Operations Research, 1959, The Technology Press. Morse uses eigenvectors to obtain his results.

still operate, and M is the total number of states.

(2) After many runs, what is the probability of the bus not breaking down, i.e., what is the utility of the bus? This will be obtained in the solution.

SOLUTION

Doctrine 1.

$$P = \begin{bmatrix} 1-a & a \\ 1 & 0 \end{bmatrix}$$

$$[I - zP] = \begin{bmatrix} 1-z(1-a) & -za \\ -z & 1 \end{bmatrix}$$

$$[I - zP]^{-1} = \begin{bmatrix} \frac{1}{(1+za)(1-z)} & \frac{za}{(1+za)(1-z)} \\ \frac{z}{(1+za)(1-z)} & \frac{1-z(1-a)}{(1+za)(1-z)} \end{bmatrix}$$

Using partial fractions:

$$[I - zP]^{-1} = \begin{bmatrix} \frac{a/(1+a)}{1+za} + \frac{1/(1+a)}{1-z} & \frac{-a/(1+a)}{1+za} + \frac{a/(1+a)}{1-z} \\ \frac{-1/(1+a)}{1+za} + \frac{1/(1+a)}{1-z} & \frac{1/(1+a)}{1+za} + \frac{a/(1+a)}{1-z} \end{bmatrix}$$

$$z^{-1} ([I - zP]^{-1}) = \frac{1}{1+a} \begin{bmatrix} 1 - (-a)^{n+1} & a + (-a)^{n+1} \\ 1 - (-a)^n & a + (-a)^n \end{bmatrix}$$

This points out an error in the solution of this example in Morse's article. The top line of page 100 should read:

$$(1) m^n = \frac{1}{1+a} \begin{bmatrix} 1 & a \\ 1 & a \end{bmatrix} + \frac{(-a)^n}{1+a} \begin{bmatrix} a - a \\ -1 & 1 \end{bmatrix} = \dots$$

Then the results of both authors agree:

Now n_s can be computed:

$$n_s = \sum_{n=0}^{n-1} P^n_{ii} = \frac{N}{1+a} + a \frac{1 - (-a)^n}{(1+a)^2}$$

P^n can be represented as the sum of two matrices as in equation (1). The effect of the second matrix diminishes as n gets $\gg 0$, so after many runs P^n becomes independent of n .

$$\frac{1}{1+a} \begin{bmatrix} 1 & a \\ 1 & a \end{bmatrix} \text{ is called the steady state transition matrix.}$$

Note that each row is identical. The elements p_{ij} of any row i represent the steady state probabilities of being in state j . For doctrine 1, then, the utility of the bus is $1/(1+a)$.

Doctrine 2.

$$P = \begin{bmatrix} 1-a & a & 0 \\ 0 & 1-b & b \\ 0 & 0 & 1 \end{bmatrix}$$

$$[I - zP]^{-1} = \begin{bmatrix} \frac{1}{1-z(1-a)} & \frac{az}{[1-z(1-a)][1-z(1-b)]} & \frac{abz^2}{Kz} \\ 0 & \frac{1}{1-z(1-b)} & \frac{bz}{[1-z(1-b)][1-z]} \\ 0 & 0 & \frac{1}{1-z} \end{bmatrix}$$

where $K = (1-z(1-a))(1-z(1-b))(1-z)$.

Using partial fractions:

$$[I - zP]^{-1} =$$

$$\begin{bmatrix} \frac{1}{1-z(1-a)} , & \frac{a/(b-a)}{1-z(1-a)} + \frac{a/(a-b)}{1-z(1-b)} , & \frac{a/(a-b)}{1-z(1-b)} + \frac{-b/(b-a)}{1-z(1-a)} + \frac{1}{1-z} \\ 0 , & \frac{1}{1-z(1-b)} , & \frac{-1}{1-z(1-b)} + \frac{1}{1-z} \\ 0 , & 0 , & \frac{1}{1-z} \end{bmatrix}$$

$$z^{-1}([I - zP]^{-1}) = P^n = \begin{bmatrix} (1-a)^n , & a \frac{(1-b)^n - (1-a)^n}{a+b} , & 1 + \frac{b(1-a)^n - a(1-b)^n}{a-b} \\ 0 , & (1-b)^n , & 1 - (1-b)^n \\ 0 , & 0 , & 1 \end{bmatrix}$$

$$\begin{aligned} \text{so } n_s &= \sum_{n=0}^{N-1} \left[P^n_{11} + P^n_{12} \right] \\ &= \frac{a^2 [1 - (1-b)^N] - b^2 [1 - (1-a)^N]}{ab(a-b)} \end{aligned}$$

Breaking P^n into two matrices:

$$P^n = \begin{bmatrix} 0 & 0 & 1 \\ 0 & 0 & 1 \\ 0 & 0 & 1 \end{bmatrix} + \begin{bmatrix} (1-a)^n & a \frac{(1-b)^n - (1-a)^n}{a-b} & \frac{b(1-a)^n - a(1-b)^n}{a-b} \\ 0 & (1-b)^n & -(1-b)^n \\ 0 & 0 & 0 \end{bmatrix}$$

so, if N is large, the utility of the bus is zero.

RECOMMENDATIONS

As before stated, this Technical Note is not a development of the theory of Z-transforms, but an application of them to Markov Chain theory.

Markov Chains are useful for analyzing any probabilistic or random process which may take on a finite number of possible states. Examples of such processes are:

1. Machine maintenance. Here, the breakdown of operating machines is random. The states may be "operating" and "non-operating".
2. Inventory control. Demands for maintenance materials, construction materials, etc. are random. The states of an inventory system might be inventory levels.
3. Replacement of items that fail. Light bulbs in a building fail at random times. A Markov Chain can be used to represent this process. The states of the process are perhaps the number of light bulbs which have failed.

Since so many such random processes occur it is not difficult to find other applications within the sphere of Shore Operation maintenance.

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author) U. S. Naval Civil Engineering Laboratory Port Hueneme, California		2a. REPORT SECURITY CLASSIFICATION
		2b. GROUP
3. REPORT TITLE Application of Z-Transform Methods to Markov Chain Problems, with a Maintenance Example		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Interim Continuing project		
5. AUTHOR(S) (Last name, first name, initial) Love, Stephen F.		
6. REPORT DATE 22 October 1964	7a. TOTAL NO. OF PAGES 9	7b. NO. OF REFS None
8a. CONTRACT OR GRANT NO. b. PROJECT NO Y-F015-15-06-504 c. d.		9a. ORIGINATOR'S REPORT NUMBER(S) TN-652 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this Technical Note from OOC		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Bureau of Yards and Docks
13. ABSTRACT This Technical Note develops an application of the theory of the Z-transform to the problem of finding the nth power of a transition matrix, motivated by the need of such a solution in the theory of Markov Chains. To illustrate the theory, an example involving vehicle maintenance is presented in detail. The results of the example may be compared with those of Philip M. Morse, "Markov Processes", in <u>Notes on Operations Research</u> , 1959, The Technology Press, Massachusetts Institute of Technology.		

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Z-transform Markov Chains Maintenance Vehicles	8 4		8 9			

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.